

## Custom Anodized Sheet & Coil Capability - Lawrence & Frederick

<b>Anodizing Type</b>	Sulfuric Acid ( Mil-A-8625F )	
	Phosphoric Acid	
<b>Class</b>	Class I (Dyed)	
	II (Undyed)	
<b>Process - Continuous Coil</b>	Pre-Clean	Sealed
	Dull / Brighten	Rinse
	Anodize	Rewound
	Color / Dye	
<b>Form</b>	Continuous Coil	
<b>Materials</b>	Aluminum	
<b>Alloys</b>	1000 Series	
	5000 Series	
	3000 Series	
<b>Tempers</b>	All	
<b>Finish</b>	Mill (MX)	Short-line Brush (YX)
	Scratch Brush / Matte (SX)	Specular (OB)
	Bright (BX)	Etched/Matte (MH)
	Long-line Brush (VX)	Satin (MM)
<b>Colors</b>	Clear	
	Unsealed	
	Colors	
<b>ID Fiber Core Diameter</b>	.012 - .063 - 16" or 20" ID fiber	
	.002 - .008 - 3" or 6" Fiber	
<b>Sheet Length</b>	Up to 120"	
<b>Slit Width Coils</b>	1"to 48.5"	
<b>Thickness</b>	.002 to .063	
<b>Weight</b>	As Specified	
<b>Additional Services</b>	Contract Slitting	
	Contract Sheeting and Blanking	
	Pressure Sensitive Adhesive Application	
	Vinyl Masking	
<b>Additional Information</b>	Industry Focus	
	<u>Architectural</u>	<u>Appliance</u>
	<u>Automotive</u>	<u>Furniture</u>
	<u>Industrial Nameplate</u>	<u>Lighting</u>
	<u>Medical</u>	<u>Screen Printing</u>
	<u>Electronics</u>	<u>Signage</u>
<b>Industry Standards</b>	ISO 9001:2008 Certified	